

PRODUCT DATA SHEET

SKIMCOAT SINGLE STAR

Description	Patching of hairline cracks and smoothening of walls has always been the aesthetics requirement of masonry surfaces. Nippon SKIMCOAT SINGLE STAR has been developed to fulfill this and to counter the problem of interior surfaces.
Uses	Nippon SKIMCOAT SINGLE STAR is used as a putty for interior substrates such as: <ul style="list-style-type: none"> - Cement plasters - Concrete - Brickworks - Primed wood
Finish	Matt/ White
Features	<ul style="list-style-type: none"> - Easy application - Good adhesion - Economical - No cracking tendency under normal application
APPLICATION DATA	
Surface Preparation	Ensure the surface is clean and stable. Extremely dry and absorbent substrates should be moistened with water before applying SKIMCOAT SINGLE STAR.
Applicaton Methods	Use trowel to apply SKIMCOAT SINGLE STAR on the surface with thickness of 1 mm depend on the surface. Wait for 20 - 30 minutes or until the surface is partially settled then apply a second coat of similar thickness. Sanding the surface to give a smooth finish.
Paint Consumption	Theoretical: 20 - 25 m ² /bag (25 Kgs) depend on thickness applied
Mixing Instruction	Mix 01 bag SKIMCOAT SINGLE STAR with 9 - 10 liters of water (Use a mixer if available or adequate mixing equipment to mix for 5 - 10 minutes). Add powder to water to avoid lumpiness. Allow the mixture to stand for about 10 minutes then mix again until homogenous. Ready plaster should be used in 2 hours after mixing.
Cleaning	Wash all equipment immediately after use with clean water
Storage	SKIMCOAT SINGLE STAR is sensitive with moisture and water, keep the bags tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Dong Nai Province, Vietnam

Tel: (84).61.3836579 – 3836586 (8 lines), Fax: (84).61.3836346 - 3836349

www.nipponpaint.com

SKIMCOAT SINGLE STAR

Packing	25 Kgs/Bag
Precaution	Do not use SKIMCOAT SINGLE STAR on unstable painted surfaces, water soluble plasters or smoothing floors. Do not apply SKIMCOAT SINGLE STAR below 10°C & moisture more than 85%.
NOTE	<i>The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales & Marketing Dept. We reserve the right to modify our product data sheet without further notice.</i>

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Dong Nai Province, Vietnam

Tel: (84).61.3836579 – 3836586 (8 lines), Fax: (84).61.3836346 - 3836349

www.nipponpaint.com